TECHNICAL DATASHEET



ABclean Nov. 2022

Cleaning and defluxing solvent

PRODUCT DESCRIPTION

ABclean is a fast-drying non toxic solvent specially formulated for **cleaning**, **defluxing**, **degreasing** electronical and electrical equipment **and** stripping coated boards. ABclean is 100% Ozone Friendly.

ABclean is really efficient to **remove coating on PCBs**. ABclean dissolves very quickly acrylic and silicones varnishes.

Its performance and its speed of evaporation make it an exceptional efficient product.

ABclean has a very large range of application and this product is compatible with a large range of plastics materials.

A wide range of cleaners is available at ABchimie, including both slow and fast-drying cleaning solvents and water-based cleaning products.

FEATURES

- Non-CFC and non-halogenated cleaning solvent.
- ABclean is a dry solvent and leaves no greasy residues after evaporating.
- Excellent removal of greases, oils, flux residues and acrylic conformal coatings from PCBs.

PRODUCT USE

ABclean contains **flammable solvent** so do not spray onto live electrical equipment or other sources of ignition.

PROPERTIES

Specific Gravity @ 20°C: 0.86
Flash Point: 12°C
Residue on Evaporation: <1ppm

The solvent ABclean is compliant with REACH and RoHS regulations. If you want a certificate, please contact us (<u>info@abchimie.com</u>). Please refer to the separate Health & Safety Data Sheet for further details.



PACKAGING

ORDER CODE

1 Litre Bulk ABclean 01L 5 Litre Bulk ABclean 05L 30 Litre Bulk ABclean 30L

STORAGE AND SHELF LIFE:

Storage temperature: 5 to 30°C

A temporary lower temperature during few days (transport) doesn't distort solvent properties.

Date by use: 24 months after the date of manufacturing

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. ABchimie cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Tel: +33 (0)4 74 83 12 19 - Fax +33 (0)4 74 83 68 62